WNG Chair

Designed by Magnus Læssøe Stephensen in 1937

The WNG Chair's rounded shape is puffed up with the upholstery, which enhances its childlike chubbiness, and invites you to sit, like a baby elephant tempting you to take a ride on its back.

General information

DESCRIPTION The WNG Chair is constructed of a seat

and back in laminated molded veneer. The two parts are joined together with a steel fitting milled into the two 12mm shells. WNG chair is only available fully upholstered. The chairs padding is produced from molded (pp foam).

VERSION Fully upholstered in fabric/leather.

Base/legs: Solid oak wood with natural

colored oil surface treatment.

PRICE GROUPS 1 to 6

Sheepskin COM & COL

ACCESSORIES Felt gliders are standard.

ENVIRONMENT Parts can be separated and sorted for

recycling.

TESTS Foam is fire retardant according to

California Technical Bulletin 117. Foam according to BS 5852, Crip 5, is

available on request.

Chair fulfils the requirements in EN 16139:2013. Loading according to Test

severity L1.







Art no: 10400-10436

Dimensions

MEASUREMENTS

Seat width: 450mm Seat height: 460mm Seat depth: 400mm Back height: 300mm Chair fully width: 600mm Chair fully height: 760mm Chair fully depth: 500mm

WEIGHT SOFA

8 kg

PACKAGING TYPE

Cardboard box, Soft Masonite, PE foam

and heavy-duty plastic.

PACKAGING MEASUREMENTS W x H x D 600mm x 820mm x 550mm

WEIGHT PACKAGING MATERIAL 1.5 kg

WEIGHT-TOTAL


9.5 kg

NUMBER OF PARCELS

1 pcs. / colli

FULLY UPHOLSTERED FABRIC CONSUMPTION W X L Chair fabric: 140cm x 200cm

Chair leather: 3 m2



Cleaning & maintenance

CLEANING

For cleaning the upholstered surface, first try to brush off the dirt gently. If this is not enough, then vacuum the surface. If further cleaning of the upholstery is needed, a stain remover is recommended. The cleaning must be gentle and must always be tested on the most invisible area of the surface before the actual cleaning. Avoid blotches by gentle, circular rubbing towards the stain. To avoid stains, quickly remove the dirt with a piece of absorbing household wipe and clean with water and colorless washing-up liquid. Do not use the following products for the padding:

- Undiluted cleaning liquids.
- Bleach.
- Ammoniac.
- Soap for hard surfaces.

For dusting and light cleaning of the frame use a soft, dry cloth. For further cleaning of the frame, use a soft cloth that is firmly wrung in clean water for gently wiping the surface, and then immediately use a dry cloth to wipe the surface again. Do not use materials for maintenance that:

- Contain abrasive agents.
- Are basic, acidiferous, or organic.

For the best maintenance of the product, protect it against sunlight and heat, and try to keep it away from moisture, grease, and other dirt. Furthermore, protect the surfaces against sharp objects and other that might scratch.

MAINTENANCE

We recommend to re-oil once a year.